

PRODUCT FACT SHEET

2AA PROPOLYMER® HAZ-LO® INTRINSICALLY SAFE ALKALINE FLASHLIGHT

MARKET

APPLICATIONS: Industrial, Occupational Safety, Fire & Rescue, Sporting Goods, Law Enforcement, Security,

Hardware/Tool, Consumer

DESCRIPTION: The 2AA ProPolymer® HAZ-LO® is an extremely durable, waterproof alkaline battery-powered

intrinsically safe flashlight. This light offers a push-button tailswitch for momentary on on-off operation. Div 1 model available in black or yellow. ATEX model available in orange and yellow.

CASE MATERIAL: Body: Impact resistant Engineering polymer.

Facecap: Impact resistant Engineering polymer overmolded onto polycarbonate lens.

DIMENSIONS: Length: 6.40 in. (16.26 cm) Major Diameter: 1.32 in. (3.35 cm) Body Diameter: 0.89 in. (2.26 cm)

WEIGHT: 3.6 oz (100 grams) with batteries (included in purchase).

LENS: Unbreakable polycarbonate with scratch-resistant coating.

LIGHT SOURCE: C4® LED technology, impervious to shock with a 50,000 hour lifetime.

LIGHT OUTPUT: 65 lumens, 2,300 candela peak beam intensity and 96 meter beam distance.

Smooth parabolic reflector produces a tight beam with optimal peripheral illumination.

RUN TIME:

24 hours to 10% of initial lumen output. See performance curve.

ON/OFF: Push button tail switch provides one handed momentary or constant "on" operation.

BATTERIES: Two (2) 1.5V alkaline batteries.

FEATURES: C4® LED technology.

Sealed construction.

Intrinsically safe.

IPX7 rated design; waterproof to 1 meter for 30 minutes.

1 meter impact resistance tested.

Push button tailswitch for momentary and constant on operation.

Integrated clip.

APPROVALS*:

SGS

Class I, II, Division 1, Groups A, B, C, D, E, F, G; Class III; CL I, ZN 0, IIC; T-Class: T4 (approved for use with Energizer E91, Duracell MN1500 and Rayovac NO.815)



Permissible Flashlight. Approval No. 20-A140002-0. Tested for Intrinsic Safety in Methane-Air mixtures only.

(approved for use with Energizer E91, Duracell MN1500 and Rayovac NO.815)



II 1G Ex ia IIC T3/T4 Ga (approved for use with Duracell MN1500 (T3) and Rayovac NO.815 (T4) BASEEFA 14ATEX0072: IECEX BAS 14.0034



Ex ia IIC T3/T4 Ga (approved for use with Duracell MN1500 (T3) and Rayovac NO.815 (T4) DNV 15.0170X

Meets applicable European Community Directives.

Streamlight's Limited Lifetime Warranty

PERFORMANCE CURVE

WARRANTY: OPTIONAL

ACCESSORIES: Helmet Mounts, Safety Wands, Holster

7 0 6 12 18 24 HOURS

All performance claims tested to ANSI/NEMA FL1-2009 Standard

Issued: 05/08/2014

Revised: 05/04/2016 **Rev:** 4 Made In China **Document #186**

^{*} See product for specific ratings.