

## PRODUCT FACT SHEET

## STINGER® LED or STINGER DS® LED RECHARGEABLE FLASHLIGHT

MARKET

LUMENS 26,000 cd

ON/OFF:

APPLICATIONS: Law Enforcement, Sporting Goods, Security, Fire & Rescue, Hardware/Tool, Automotive, Industrial, Consumer

**DESCRIPTION:** Compact & extremely powerful, the Stinger® LED and Stinger DS® LED rechargeable flashlights offer 3

microprocessor controlled intensity modes, strobe mode and the latest in power LED technology.

The Stinger DS® LED includes a second independent easy to locate tactical tailcap switch. The combination of rechargeable batteries and the C4® LED results in one of the lowest operating costs of any flashlight made.

CASE MATERIAL: 6000 series machined aircraft aluminum with non-slip rubberized comfort grip with anti-roll rubber ring.

**DIMENSIONS:** Stinger® LED Length: 8.41 in. (21.36 cm) Diameter: Major Diameter: 1.62 in. (4.11 cm)

Stinger DS® LED Length: 8.85 in. (22.48 cm)

Body Diameter: 1.17 in. (2.97 cm)

WEIGHT: Stinger® LED: 12.4 oz (352 grams)\* Stinger DS® LED: 12.8 oz (364 grams)\*

LIGHT SOURCE: Unbreakable polycarbonate with scratch-resistant coating. O-ring sealed.

LIGHT SOURCE: High power LED, white, impervious to shock with a 50,000 hour lifetime.

**LIGHT OUTPUT:** See Chart. Optimized electronics provide regulated intensity.

Deep-dish parabolic reflector produces a concentrated beam with optimum peripheral illumination.

Multi-function, easy access head mounted push-button switch designed for extremely long life; tested at 1

million actuations. Stinger DS® LED provides a second multi-function push-button tactical tailswitch where both switches offer full feature control independent of each other.

RUN TIME: | ( ) | See Chart. All claims to 10% of initial lumen output. Strobe: 7.50 continuous hours.

BATTERY: 3-cell, 3.6 Volt, 2.6Ah NiMH sub-C battery, rechargeable up to 1000 times.

CHARGE HOLDERS: Fits existing Stinger® chargers and new Smart chargers.

Steady charger: Fully recharges within 16 hours.

Smart charger: Fully recharges within 4.5 hours (5V/1A USB input) or 3 hours (12VDC input).

Smart PiggyBack® charger: Fully recharges within 7.5 hours (5V/1A USB input) or 4 hours (12VDC input).

CHARGE CORDS: Streamlight universal AC input voltage, 5V/1A USB or 12.7V/.8A output charge cords available with IEC Type A

(US & Japan), Type C (Euro), Type G (UK) or Type I (Australia) plugs.

12VDC cigarette lighter or direct wire automotive cords.

**FEATURES:** High power LED for extreme brightness.

IPX4 Rated for water resistant operation.

1 meter impact resistance tested.

Serialized for positive identification.

LED Charge-continuity indicator on charger base. Compact, snap-in charger mounts in any position.


WARRANTY: Streamlight's Limited Lifetime Warranty.


**APPROVALS: ( E** Meets applicable European Community Directives.

(BC) CEC Compliant (Smart charger models only)

OPTIONAL Safety wands, ring holder, holster, color filters, 2.6Ah Li-Ion battery, 5-unit bank charger, Smart charger, ACCESSORIES: Steady charger or Smart Piggy-Back® charger that allows for simultaneous charging of light and battery.

Steady charger or Smart Piggy-Back® charger that allows for simultaneous charging of light and battery.





\*With battery (included in purchase)

All performance claims to ANSI/PLATO FL1-2016 Standard

Issued: 10/13/2006 Revised: 05/08/2019 Rev: 11