

## PRODUCT FACT SHEET

## STRION® LED

## HIGH PERFORMANCE RECHARGEABLE FLASHLIGHT

**MARKET** 

APPLICATIONS: Premium Professional Light - Law Enforcement, Industrial, Security, Outdoor, Consumer

**DESCRIPTION:** Ultra compact & powerful, the Strion® LED rechargeable flashlight offers 3 microprocessor

controlled variable intensity modes, strobe mode and the latest in power LED technology. The combination of rechargeable batteries and the C4® LED results in one of the lowest operating

costs of any flashlight made.

CASE MATERIAL: 6000 series machined aircraft aluminum with anodized finish. Available in Black.

**DIMENSIONS:** Length: 5.90 in. (14.99 cm) Head Diameter: 1.25 in. (3.18 cm)

Barrel Diameter: 0.95 in. (2.41 cm) Diameter at Tri-Lobe Anti-Roll Flange: 1.35 in. (3.43 cm)

**WEIGHT:** 5.2 oz (148 grams) with battery

**LENS:** Borofloat High Temperature Glass. Gasket sealed.

**LIGHT SOURCE:** C4® LED technology, impervious to shock with a 50,000 hour lifetime.

**LIGHT OUTPUT:** See chart. Optimized electronics provides regulated intensity.

1375 LUMENS 12,000 cd

ON/OFF:

Multi-function, push-button tactical tailswitch. One handed operation of momentary, variable

intensity or strobe mode.

RUN TIME: BATTERY:



See chart. All claims to 10% of initial lumen output. Strobe: 6.5 continuous hours.

Lithium Ion with on-board safety control circuit, 3.63V, 2600mAh, rechargeable up to 1000 times.

**CHARGING:** Fits existing Strion® chargers.

Clamp style charge holder with digital control circuit that prevents overcharge.

Fully recharges battery in 3.5 hours and charges battery in product.

Charge base LED indication: LED Steady - Charging; LED Blinking - Charged.

**FEATURES:** 



C4® LED technology for extreme brightness. IPX4 rated design; water resistant operation.

2 meter impact resistance tested.

LED Charge-continuity indicator on charger base. Compact, snap-in charger mounts in any position.

Serialized for positive identification.

**WARRANTY:** Streamlight's Limited Lifetime Warranty.


**APPROVALS:** ( Meets applicable European Community directives.

(BC) CEC Compliant

OPTIONAL

ACCESSORIES: Color Filters, Safety Wands, Holster, Rail Mount, Piggyback® Charger, 6 Unit Bank Charger.

1	FL1 STANDARD	HIGH	MEDIUM	LOW
OUTPUT	31/2	375 LUMENS	175 LUMENS	80 LUMENS
RUNTIME	0	2h 30min	4h 45min	9h 30min
DISTANCE		219m	161m	113m
INTENSITY		12,000cd	6,500cd	3,200cd



All performance claims tested to ANSI/PLATO FL1-2016 Standard

Issued: 10/27/2008

Revised: 10/24/2018 Rev: 10 Assembled in The USA. Document #245