

PROTAC® RAIL MOUNT 2

- DESCRIPTION:** Lightweight, low-profile, gun-mounted tactical light powered by CR123A lithium or AA batteries. The CR123A battery provides 2 hours of continuous run time on high and over 20 hours on low. The rail clamp is designed to securely attach/detach from rifles, carbines, and submachine guns with a MIL-STD-1913 rail. The included M-LOK® mount allows for alternative mounting options to M-LOK and M-LOK compatible rail systems.
- CASE MATERIAL:** 6000 Series machined aircraft aluminum with black anodized finish
- DIMENSIONS:** Length: 5.00 in (12.7 cm) Width: 1.20 in (3.04 cm) Height: 1.50 in (3.81 cm)
- WEIGHT:** 5.0 oz (141.7 g) with batteries (included in purchase)
- LENS:** High-temperature, shock-mounted, AR coated, impact-resistant BOROFLOAT® glass
- LIGHT SOURCE:** White LED impervious to shock with a 50,000-hour lifetime
- LIGHT OUTPUT:** High - 625 lumens; 22,000 candela peak beam intensity; 297 m beam distance
Low - 60 lumens; 2,000 candela peak beam intensity; 89 m beam distance
- TIR optic produces a concentrated beam with optimum peripheral illumination.
- ON/OFF:** Multi-function, push-button tactical tail switch or dual remote pressure switch with latching push-button. One-handed operation of momentary, variable intensity, or strobe mode. TEN-TAP® programmable switch to allow for user selection of one of three different programs: high/strobe (factory default), high only, or low/high.
- RUN TIME:** High - 1.5 hours of regulated run time and 2 hours to 10% output
Low - 18 hours of regulated run time and 21 hours to 10% output
Solid-state current regulation for consistent illumination level.
- BATTERY:** Two (2) 3-volt CR123A lithium batteries with a storage life of 10 years
- FEATURES:** Push-button tail switch features momentary/constant on operation
One-handed snap-on and tighten interface keeps hands away from muzzle when attaching/detaching from the firearm
Securely fits a broad range of weapons
Mounts directly to guns with MIL-STD-1913 (Picatinny) rails or M-LOK and M-LOK compatible rail systems
Extensively live fire tested, impact-resistant construction
IP67-rated with standard push-button switch installed; waterproof to 1 meter for 30 minutes
IP54-rated with remote pressure switch installed
- APPROVALS:**   Meets applicable United Kingdom and European Community Directives
 CEC Compliant
- WARRANTY:** Streamlight's Limited Lifetime Warranty
- OPTIONAL ACCESSORIES:** Red, blue, and green filters