

PRODUCT FACT SHEET

STRION® DS HPL

HIGH LUMEN LONG RANGE DUAL SWITCH RECHARGEABLE FLASHLIGHT

MARKET

APPLICATIONS: Premium Professional Light - Law Enforcement, Industrial, Security, Outdoor, Consumer

DESCRIPTION: Ultra compact & powerful, the Strion® DS HPL rechargeable flashlight offers two independent easy to

> locate switches. 3 microprocessor controlled variable intensity modes, strobe mode and the latest in high power LED technology. The Strion® DS HPL also offers three different user selectable programs. The combination of rechargeable batteries and high power LED results in one of the lowest operating

costs of any flashlight made.

CASE MATERIAL: 6000 series machined aircraft aluminum with anodized finish. Available in Black.

DIMENSIONS: Length: 7.56 in (19.20 cm) Major Diameter: 2.20 in. (5.59 cm)

Barrel Diameter: 0.95 in. (2.41 cm)

WEIGHT: 6.9 oz (196 grams) with battery (included in purchase)

LENS: Unbreakable polycarbonate lens with scratch-resistant coating. O-ring sealed. LIGHT SOURCE: High power LED, white, impervious to shock with a 50,000 hour lifetime.

LIGHT OUTPUT: See chart. Optimized electronics provides regulated intensity.

Deep-dish parabolic reflector produces a long range beam with optimal peripheral illumination.

ON/OFF:

Multi-function, easy-access head mounted push-button switch and second multi-function push-button tactical tailswitch where both switches offer full feature control independent of each other. One handed operation of momentary, variable intensity or strobe mode using either switch. Switches designed for extremely long life; tested at 1 million actuations. TEN-TAP® programmable switch allows user selection of one of three different programs: high/medium/low with strobe (factory default), high only without strobe, or high/medium/low without strobe.

RUN TIME: BATTERY:



See chart. All claims to 10% of initial lumen output. Strobe: 2.5 continuous hours.

Lithium Ion with on-board safety control circuit, 3.63V, 2600mAh, rechargeable up to 1000 times.

CHARGING: Fits existing Strion® chargers.

Clamp style charge holder with digital control circuit that prevents overcharge.

Fully recharges battery in 3.5 hours and charges battery in product.

Charge base LED indication: LED Steady - Charging; LED Blinking - Charged.

FEATURES:



High power LED for extreme brightness.

IPX4 rated design; water resistant operation.

2 meter impact resistance tested.

TEN-TAP® programmable switch allows user to select one of three different programs.

LED Charge-continuity indicator on charger base. Compact, snap-in charger mounts in any position.

Serialized for positive identification.

WARRANTY: Streamlight's Limited Lifetime Warranty.

Meets applicable European Community directives. APPROVALS:

CEC Compliant

OPTIONAL

ACCESSORIES: Safety Wands, Holster, Rail Mount, Piggyback® Charger, 6 Unit Bank Charger.


OUTPUT

RUNTIME

DISTANCE

INTENSITY

FL1 STANDARD	HIGH	MEDIUM	LOW
31/2	700 LUMENS	300 LUMENS	40 LUMENS
0	1h15min	3h30min	24h
	420m	268m	102m
	44,000cd	18,000cd	2,600cd



All performance claims tested to ANSI/PLATO FL1-2016 Standard

Issued: 06/22/2016 Revised: 05/08/2019 Rev: 3