

SL-B26[®] LI-ION USB BATTERY PACK/BANK CHARGER PROTECTED LI-ION USB RECHARGEABLE BATTERY PACK AND 8-UNIT BANK CHARGER



CHARGING

CHARGED

SL-B26[®] PROTECTED LI-ION USB RECHARGEABLE BATTERY PACK

- Dims/Weight Length: 2.75 in (7.0 cm); Diameter: 0.744 in (1.89 cm) maximum 1.7 oz. (48g)
- Battery Lithium Ion with on-board safety control circuit, 3.7V, 2600mAh, charges in 5 hours.
- Charge Input Micro-USB input charges from Streamlight AC/USB adapters and most other USB sources or Li-ion charge cradle.

Features - Charge status indicator

- Integrated safety circuit protects batteries from overdischarge and overcharge
- Additional safety features: pressure vent and built in PTC surge protector
- Warranty Streamlight's Limited 2 Year Warranty. Visit streamlight.com for full warranty information.

ITEM	1PK	2PK	8PK
SL-B26 Battery Pack	#22101	#22102	#22105
SYSTEM	CLAM	BOX	
Siege X USB - Coyote		#44956	
ProTac HL5-X USB	#88080	#88081	
ProTac 2L-X USB	#88082	#88083	
ProTac HL-X USB	#88084	#88085	
PolyTac X USB - Black	#88610	#88613	
PolyTac X USB - Yellow	#88611	#88614	
PolyTac X USB - Coyote	#88612	#88615	
Vantage 180X USB - Orange		#88911	
Vantage 180X USB - Black		#88913	
PolyTac 90X USB - Black		#88835	
PolyTac 90X USB - Yellow		#88836	
PolyTac 90X USB - Orange		#88838	
PolyTac 90X USB - Org w/ Gear Keeper		#88837	
ProTac 90X USB - Black		#88095	
Survivior X USB - Orange		#90044	
Survivior X USB - Yellow		#90244	



Charge indicators over each battery slot Red = charging, Green = charged



AC/DC power input

8-UNIT BANK CHARGER

Case Material	Impact resistant engineered polymer housing available in black.
Dims/Weight	Length: 10.45 in (26.54 cm) Width: 4.75in. (12.06 cm) Height: 1.00 in (2.54 cm) Weight: 7.61 oz. (216 grams) no batteries 20.88 0z. (592 grams) with batteries
Battery	SL-B26 [®] protected Li-lon USB rechargeable battery pack
Charge Input	120V AC or International power supply wall adapter or 12V DC direct wire with 2.5mm barrel plug are available to connect with the charger.
Charge Time	Eight bay: 5.25 hours. Green and Red LED charge indicator for quick visual notification of charge status.
Features	Charger temperature safety circuit prevents damage to batteries while charging.
Warranty	Streamlight's Limited Lifetime Warranty. Streamlight warrants this product to be free of defects for a lifetime of use except for batteries and bulbs, abuse and normal wear. We will repair, replace or refund the purchase price of this product should we determine it to be
	defective. This limited lifetime warranty also excludes rechargeable batteries, chargers, switches and electronics which have a 2 year warranty with proof of purchase. THIS IS THE ONLY WARRANTY, EXPRESSED OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PUR- POSE. INCIDENTAL, CONSEQUENTIAL OR SPECIAL DAMAG- ES ARE EXPRESSLY DISCLAIMED EXCEPT WHERE SUCH LIMITATION IS PROHIBITED BY LAW. You may have other specific legal rights which vary by jurisdiction. Visit streamlight.com for full warranty information.

vals Meets applicable United Kingdom and European Community Directives. CEC compliant. Meets requirements of NFPA 1901-14.1.10.2 (2016) mounted in upright position.

ITEM	UPC	BOX
8-Unit Bank Charger - 12V DC	080926-20220-7	20220
8-Unit Bank Charger - 120V/100V AC	080926-20221-4	20221
8-Unit Bank Charger - 230V/240V AC	080926-20222-1	20222
8-Unit Bank Charger - with batteries - 12V DC	080926-20223-8	20223
8-Unit Bank Charger - with batteries - 120V/100V AC	080926-20224-5	20224
8-Unit Bank Charger - with batteries - 230V/240V AC	080926-20225-2	20225

Assembled in USA

	ltem	UPC	Part #
	12V DC 2 Li-Ion Bank Charger Cord	080926-20226-9	20226
	Li-Ion Bank Charge Cradle	080926-22100-0	22100
	40" (101 cm) USB Cord	080926-22070-6	22070
	22" (55.88 cm) USB Cord	080926-22081-2	22081
Carton	120V AC USB Charge Cord	080926-22071-3	22071
	230V AC USB Charge Cord	080926-22072-0	22072
	240V AC USB Wall Adapter	080926-22049-2	22049
	120V AC Cord Li-Ion Bank Charger/Waypoint (Rechargeable)/Super Siege	080926-44909-1	44909
	Int'l Charge Cord - 230V/240V (UK)/120V AC	080926-44919-0	44919
	240V AC (AUS/NZ) Blade* for use with 44919 Int'l Cord	080926-44926-8	44926