



SIDEWINDER COMPACT® II WITH NVG MOUNT MULTI-BATTERY MULTI-SOURCE HANDS-FREE FLASHLIGHT



Sidewinder (Aviation) NVG Mount #14135

- Easy non-permanent attachment to NVG bracket on **HGU-84 rotary wing aircrew helmet** without tools
- Quick attachment/release of all Sidewinder series lights without tools
- Compound action design provides one handed installation and removal of lighting source without buttons or levers. Light is secured without risk of impact loss
- Full 360 degree rotation of lighting source
- 16 detent locations for accurate placement of lighting source
- Withstands 70lb pull test
- Construction: high-impact super tough glass re-enforced nylon case. Hardware made from stainless steel for exceptional durability and weather resistance
- Streamlight warrants its Sidewinder NVG Mount will be free from manufacturing defects under normal use for 12 months after purchase. During the warranty period, at its sole discretion, Streamlight will repair or replace any defective part or product



Sidewinder (Tactical) NVG Mount #14155

- Easy non-permanent attachment to fixed NVG shroud of most **DoD, NATO and ISAF combat helmets** without tools
- Quick attachment/release of all Sidewinder series lights without tools
- Compound action design provides one handed installation and removal of lighting source without buttons or levers. Light is secured without risk of impact loss
- Full 360 degree rotation of lighting source
- 16 detent locations for accurate placement of lighting source
- Withstands 50lb pull test
- Construction: high-impact super tough glass re-enforced nylon case. Hardware made from stainless steel for exceptional durability and weather resistance
- Streamlight warrants its Sidewinder NVG Mount will be free from manufacturing defects under normal use for 12 months after purchase. During the warranty period, at its sole discretion, Streamlight will repair or replace any defective part or product

Sidewinder Compact II

Case Material: High impact super tough nylon case offers exceptional durability and weather resistance. All openings are O-ring sealed

Dims/Weight: Length: 3.00 in. (7.62 cm); Width: 1.07 in. (2.72 cm); Depth: 2.04 in. (5.21 cm); 2.4 ounces (68 grams)

Light Source/output: White C4 LED w/AA: 47 lumens; 1,000 candela; 63m beam distance
5mm IR LED: 25mW/sr (min) radiant intensity
5mm Red LED: 1.5 lumens; 60 candela; 15m beam distance
5mm Blue LED: 1.8 lumens; 130 candela; 23m beam distance
5mm Green LED: 4.5 lumens; 68 candela; 16m beam distance

AA Alkaline Battery LED Type	Low (10% Output)	Medium 1 (25% Output)	Medium 2 (45% Output)	High (100% Output)	Strobe (100% Output)
White C4®	40 Hours	16 Hours	8 Hours	2 Hours	4 Hours
5mm IR or Red	100+ Hours	48 Hours	18 Hours	9 Hours	14 Hours
5mm Blue or Green	100+ Hours	36 Hours	12 Hours	6 Hours	10 Hours

On/Off/Intensity Mode Selection:

Compound On-Off mode selector switch ergonomically separates On-Off-Dimming-Strobe and LED selection functions. Design does not require the operator to access separate switching locations on the device. Rubber dome actuator and 4 position pull-to-turn locking rotary selector knob with IR LED tactile indicator provides easy operation even when wearing heavy gloves

CR123 / AA Lithium Battery LED Type	Low (10% Output)	Medium 1 (25% Output)	Medium 2 (45% Output)	High (100% Output)	Strobe (100% Output)
White C4®	70 Hours	28 Hours	16 Hours	6 Hours	10 Hours
5mm IR or Red	100+ Hours	72 Hours	36 Hours	16 Hours	24 Hours
5mm Blue or Green	100+ Hours	60 Hours	24 Hours	12 Hours	18 Hours

Battery: Includes one AA alkaline battery; also accepts one CR123A lithium or AA lithium battery. Lithium batteries allow operation in extreme temperature environments (-40F to 140F)

Approvals: Meets applicable European Community Directives

Warranty: Streamlight warrants its Sidewinder Compact (excepting batteries) will be free from manufacturing defects under normal use for 12 months after purchase. During the warranty period, at its sole discretion, Streamlight will repair or replace any defective part or product.

Features:

Push button switch specified to 300K operations	3 meter multiple orientation impact resistance tested
Pull-to-turn locking rotary knob prevents accidental mode changes	Cord attachment holes provided in battery compartment cover capable of supporting 25 lbs of load
Push button switch enables/disables selected illumination source starting at low output and progressing to the brightest output in 4 discrete steps (Sportsman's model enables selected illumination source starting at high output and progressing to the dimmest output). Double click of push button initiates high output strobe of selected illumination source.	Tactile battery polarity indicators for battery replacement in the dark. Built in battery polarity protection guards against damage to the light IPX7 Rated design; waterproof to 1 meter for 30 minutes. O-Ring and gasket sealed openings. Meets MIL-STD-810F, Method 512.4.

See reverse for part numbers and additional accessories

Item	UPC	Part #
Military Model Each LED features 4 levels of increased output intensities: Low, Medium, Medium-High, High, plus Strobe. White C4 LED, Red, Blue, IR LEDs		
Sidewinder Compact II Military Model -White C4 LED, Red, Blue, IR LEDs includes CR123A lithium battery. Boxed	080926-14516-0	14516
Sidewinder Compact II Military Model -White C4 LED, Red, Blue, IR LEDs includes helmet mount and CR123A lithium battery. Boxed	080926-14510-8	14510
Sidewinder Compact II Military Model -White C4 LED, Red, Blue, IR LEDs includes helmet mount, headstrap and CR123A lithium battery. Clam	080926-14512-2	14512
Sidewinder Compact II Military Model -White C4 LED, Red, Blue, IR LEDs includes E-mount, headstrap and CR123A lithium battery. Clam	080926-14513-9	14513
Sidewinder Compact II Military Model -White C4 LED, Red, Blue, IR LEDs includes helmet mount, headstrap and CR123A lithium battery. Boxed	080926-14514-6	14514
Sidewinder Compact II Military Model -White C4 LED, Red, Blue, IR LEDs includes helmet mount, rail mount and CR123A lithium battery. Boxed	080926-14518-4	14518
Sidewinder Compact II Military Model White C4 LED, Green, Blue, IR LEDs. Includes NVG mount (works with DoD, NATO and ISAF combat helmets) and one CR123A lithium battery. Boxed.	080926-14515-3	14515
Aviation Model Each LED features 4 levels of increased output intensities: Low, Medium, Medium-High, High, plus Strobe. White C4 LED, Green, Blue, IR LEDs		
Sidewinder Compact II Aviation Model White C4 LED, Green, Blue, IR LEDs. Includes rail mount, headstrap and one CR123A lithium battery. Clam	080926-14531-3	14531
Sidewinder Compact II Aviation Model White C4 LED, Green, Blue, IR LEDs. Includes rail mount, headstrap and one "AA" alkaline battery. Boxed.	080926-14532-0	14532
Sidewinder Compact II Aviation Model White C4 LED, Green, Blue, IR LEDs. Includes NVG mount (works with HGU-84 rotary wing aircrew helmet) and one "AA" alkaline battery. Boxed.	080926-14533-7	14533



Item	UPC	Part #
Replacement MOLLE Retainer - Sidewinder	080926-14030-1	14030
Sidewinder Helmet Mount - Coyote	080926-14055-4	14055
Sidewinder 1913 Rail Mount (not intended for use with long guns) - Coyote	080926-14057-8	14057
Elastic Headstrap - Coyote. Works with Sidewinder Compact and PolyTac 90	080926-14059-2	14059
Sidewinder Helmet Mount Accessory Kit	080926-14112-4	14112
Sidewinder Rail Mount Accessory Kit	080926-14113-1	14113
Sidewinder NVG Mount (works with HGU-84 rotary wing aircrew helmet)	080926-14135-3	14135
Sidewinder NVG Mount (Tactical) (works with DoD, NATO and ISAF combat helmets)	080926-14155-1	14155

Item	UPC	Part #
Sidewinder E-Mount Kit (ACH, ECH, MICH, LWH Compatible)	080926-14136-0	14136
Sidewinder E-Mount Accessory Kit - includes E-mount, MOLLE retainer and paracord	080926-14137-7	14137
Paracord - Sidewinder	080926-14138-4	14138
Sidewinder Rescue Accessory Kit - includes MOLLE retainer and paracord	080926-14139-1	14139
Safety Wand - Glow in the Dark - Sidewinder Series	080926-14902-1	14902
Lithium batteries (2) Pack	080926-85175-7	85175
Lithium batteries (12) Pack	080926-85177-1	85177
Lithium batteries (400) Pack	080926-85179-5	85179
Lithium batteries (6) Pack	080926-85180-1	85180